



# GasAlert MicroClip

multi-gas detectors



## Multi-gas made easier

The easy to wear, slim and compact GasAlertMicroClip provides affordable protection from atmospheric gas hazards. For standard operation with features you can count on, opt for the GasAlertMicroClip XT. For extended battery life, especially in cold weather, choose the GasAlertMicroClip XL. Both offer visual compliance at a glance with the flashing, green IntelliFlash™. Easy one-button operation reduces training time and lets workers focus on the job at hand. For simple, cost-effective management of your records, calibration and bump testing, choose BW Technologies by Honeywell's MicroDock II automatic test and calibration system and Fleet Manager II software.



Black housing available



Easily download datalogged info



Simple calibration and bump testing

H<sub>2</sub>S

CO

O<sub>2</sub>

LEL

GasAlert  
**MicroClip XL**

GasAlert  
**MicroClip XT**

**WATER  
RESISTANT** 

- Easy and comfortable to wear; thin and lightweight
- Easy operation and straightforward training with one-button simplicity
- Easy visual compliance with flashing, green IntelliFlash™
- Easy and cost effective to own




**BW**  
Technologies  
by Honeywell

**Wear yellow. Work safe.**

### Additional GasAlertMicroClip features:

- Choose the GasAlertMicroClip XL for cold weather performance
- IntelliFlash™ verifies operation and compliance to both the user and supervisor
- Tamper-proof, one button operation
- Powered by a rechargeable lithium polymer battery

### GasAlertMicroClip Specifications

	GasAlertMicroClip XL	GasAlertMicroClip XT
<b>Size</b>	4.4 x 2.4 x 1.2 in. / 11.3 x 6.0 x 3.1 cm	4.4 x 2.4 x 1.1 in. / 11.3 x 6.0 x 2.9 cm
<b>Weight</b>	6.7 oz. / 190 g	6.0 oz. / 170 g
<b>Temperature</b>	-4 to +122°F / -20 to +50°C	
<b>Humidity</b>	0% - 95% RH (non-condensing)	
<b>Alarms</b>	- Visual, vibrating, audible (95 dB) - Low, High, STEL, TWA, OL (over limit)	
<b>Tests</b>	Audible/visual alarms on activation; sensors, battery and circuitry (continuous)	
<b>Typical battery life*</b>	18 hours at 20°C / 68°F Recharges in less than 6 hours	10 hours at 20°C / 68°F Recharges in less than 4 hours
<b>Cold weather battery life</b>	After 2 years: 14 hours at 20°C / 68°F and 12 hours at -20°C / 4°F	After 2 years: 8 hours at 20°C / 68°C
<b>User options</b>	Confidence beep Set STEL interval Sensor on/off Latching alarms Safe display mode Stealth mode Calibration lock Auto zero on start up O <sub>2</sub> auto calibration on start up Set bump test interval Force bump test when overdue	IntelliFlash™ interval Combustible gas measurement (%LEL or % by volume methane) User-settable calibration gas level Force calibration when overdue Low alarm acknowledge Language choices Set custom start up message
<b>Ratings</b>	EMI/RFI: Complies with EMC Directive 2004/108/EC IP 66	
<b>Certifications and approvals</b>	 Class I, Div. 1, Gr. A, B, C, D <b>ATEX:</b>  II 1 G Ex ia IIC T4 Ga <b>IECEX:</b> Ex ia IIC T4 Ga  European Conformity	
<b>Warranty**</b>	Full two-year warranty including sensors and battery	

\*Approximately 20% capacity loss is normal with lithium polymer batteries after 500 charge cycles. Refer to the Operator's Manual for additional information.

### Standard features of BWT multi-gas products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot
- Multi-language support in English, French, German, Spanish

### Options and Accessories



MicroDock II compatible



Auxiliary filter kit



IR connectivity kit



Five unit cradle charger

For a complete list of accessories, please contact BW Technologies by Honeywell.

### Sensor Specifications

Gas	Measuring Range	Resolution
<b>H<sub>2</sub>S</b>	0-100 ppm	1 ppm
<b>CO</b>	0-500 ppm	1 ppm
<b>O<sub>2</sub>*</b>	0-30.0%	0.1%
<b>Combustible gases</b>	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm setpoints for all sensors are user adjustable. Setpoints are automatically displayed during instrument start up.  
\*GasAlertMicroClip XL is fitted with an improved O<sub>2</sub> sensor.

### Locally available from



We Save Lives



DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

### European Headquarters

Life Safety Distribution AG  
Javastrasse 2  
8604 Hegnau  
Switzerland  
Tel: +41 (0) 44.943.4300  
Fax: +41 (0) 44.943.4398

Europe +44 (0) 1295.700.300  
France +33 (0) 442.98.17.70  
Germany +49 (0) 2137.17.6522  
Middle East +971.4.4505852  
USA 1.888.749.8878

Latin America +55.11.3475.1873  
S.E. Asia +65.6580.3468  
China +86.10.6786.7305  
Australia +61.3.9464.2770  
India +91 124 4752700

[www.honeywellanalytics.com](http://www.honeywellanalytics.com) [bwesales@gasmonitors.com](mailto:bwesales@gasmonitors.com)

H\_GasAlertMicroClip\_XL\_DS01152\_V1\_08-14\_EMEA  
© 2013 Honeywell International Ltd. All Rights Reserved.